


Product Description

Fatra prefabricated round wall outlet with an integrated sleeve of a hydro-insulation foil based on PVC and with a protective grid are used in conjunction with Fatrafol PVC membrane systems to integrate wall outlet drainage points within the membrane system.

Product Dimensions



Round gutter spouts

| Type | DN | Dimensions [mm] | | | | | |
|------------|-----|-----------------|----|-----|-----|----|----|
| | | a* | b | c | d | e | f |
| TWC 50 | 50 | 600 | 20 | 104 | 88 | 13 | 20 |
| TWC 75 | 70 | 600 | 20 | 104 | 88 | 13 | 20 |
| TWC 110 | 100 | 600 | 20 | 180 | 157 | 13 | 20 |
| TWC 125 | 125 | 600 | 20 | 180 | 157 | 13 | 20 |
| TWC 160 | 150 | 600 | 20 | 180 | 157 | 13 | 20 |
| TWC 50 x0 | 50 | 64 | 20 | 104 | 88 | 13 | 20 |
| TWC 75 x0 | 70 | 64 | 20 | 104 | 88 | 13 | 20 |
| TWC 110 x0 | 100 | 84 | 20 | 180 | 157 | 13 | 20 |
| TWC 125 x0 | 125 | 84 | 20 | 180 | 157 | 13 | 20 |
| TWC 160 x0 | 150 | 84 | 20 | 180 | 157 | 13 | 20 |
| TWC MINI | 40 | 200 | 60 | 35 | 95 | 11 | 50 |

* upon order it is possible to extend up to 2,000 mm

