



### Product Description

Fatrabond 1210 insulation adhesive is a fast curing formula with an excellent high coverage rate. Fatrabond 1210 is a polyurethane moisture curing adhesive. 50% of the final strength is achieved immediately, with full strength achieved in 24 hours. It has a good moisture and weather resistance against high temperature exposure.

### Usage

Industrial canister spray adhesive formulated specifically to bond PIR Insulation boards to a variety of roof decks, including concrete, insulation boards, plywood & cementitious boards.

### Application

Adhesive should be applied to sub deck surface, allowed to dry (2-6 minutes or until dry with touch) then parts mated under pressure. Bonds should be made as soon as practically possible. If adhesive is left to dry for over 15 minutes, parts should be recoated.

Normal coverage required with a beaded spray pattern is approximately 300mm apart; however, porous surfaces may need a second coat. Initial bond is strong enough to allow cutting or trimming immediately although ultimate strength is achieved in 1-3 days.

WARNING:- Avoid direct flame or exposure to excessive heat. Do not store at temperatures over 30°C. See MSDS.

### Benefits:-

- Single sided application - Fast & efficient application with high tack - Resistant to blistering
- Single product for detail work - Excellent green strength
- High heat resistance - Green credentials - Ideal for smaller application - Portable and convenient
- Minimises project cost - Excellent cure time

### Physical Properties

Solids:	60% - 90%
Appearance:	Pink
Environmental:	Dichloromethane
Shelf Life:	12 Months
Sizes:	22ltr Canister
Coverage:	300m2 approximately (depending on application and substrate)
Open Time:	10 minutes at 20°C
Temperature Resistance:	-30 - 100°C
Application Temperature:	5 - 30°C